

| GENERAL DIMENSIONS | | |
|--------------------|--------|----|
| | INCHES | MM |
| A | | |
| B | | |
| C | | |
| D | | |
| E | | |
| F | | |
| G | | |
| H | | |
| I | | |

| ENGINE SPECS | |
|--------------------------------|-------------|
| APPLICATION | |
| NO. CYL | |
| CYL BORE | |
| STROKE | |
| MAX R.P.M | |
| AMT OF BOOST | |
| PISTON ASSEMBLY WTS | |
| ROD BEARING NO. | |
| BOLT SIZES AND MATERIAL | |
| SIZE | S OR H(WMC) |

| BEARING TANG LOCATION | | |
|---------------------------------|--|--|
| CHOOSE BL1 OR BL2 CONFIGURATION | | |
| J | | |
| K | | |
| L | | |
| M | | |
| N | | |

| BEARING TANG DIMENSIONS | | |
|-------------------------|--|--|
| O | | |
| P | | |
| Q | | |
| R | | |
| S | | |

| FEATURES | | |
|----------|-----------------------|-----------|
| | DESCRIPTION | YES OR NO |
| 1 | ANNULAR GROOVES | |
| 2 | LIPPED CAP | |
| 3 | BUSHING | |
| 4 | PE MACH/LAPPED FINISH | |
| 5 | BE MACH/LAPPED FINISH | |
| 6 | FPO | |
| 7 | SERIALIZATION | |

COMMENTS: _____

